

RAMPE DE ÎNCĂRCARE

CU BORDURĂ

Confecționat din aliaj de aluminiu 6005 conform UNI 8634.

Utilizarea europeană vehicule cu marfă la bord.



Greutatea maxima suportată în kg									
Coduri	Lungimea (mm)	Lat utilă (mm)	Lat tot (mm)	Înalt (mm) bordura	Distanța interaxe (mm)			Încărc. concentr.	Kg / pereche
					750	1000	1250		
H72/15B	1500	250	310	24	1685	1685	1685	1685	18
H72/20B	2000	250	310	24	1600	1600	1600	1265	23
H72/25B	2500	250	310	24	1360	1590	1600	1010	28
H72/30B	3000	250	310	24	1050	1180	1350	840	33
H72/35B	3500	250	310	24	849	936	1036	715	39
					1000	1250	1500		
H110/25B	2500	300	370	25	3810	3810	3810	2250	40
H110/30B	3000	300	370	25	3810	3700	3950	2050	49
H110/35B	3500	300	370	25	2700	3000	3280	1950	55
H110/40B	4000	300	370	25	2330	2500	2700	1950	63
H125/25B	2500	320	385	35	4110	4110	4110	2055	50
H125/30B	3000	320	385	35	3900	3900	3900	2055	60
H125/35B	3500	320	385	35	3200	3500	3900	2055	69
H125/40B	4000	320	385	35	2600	2800	3100	2050	79
H135/25BL	3000	350	405	29,5	6885	7200	7200	3825	85
H135/30BL	3500	350	405	29,5	5120	5858	6825	2810	92
H135/35BL	4000	350	405	29,5	4065	4520	5085	2805	104
H135/40BL	4500	350	405	29,5	3365	3670	4035	2490	117
					1500	1750	2000		
H175/40B	4000	400	480	37	5520	6135	6900	4230	123
H175/45B	4500	400	480	37	4555	4970	5465	3755	137
H175/50B	5000	400	480	37	3860	4155	4505	3370	152
H190/40B	4000	500	595	43	7700	8580	9650	5855	160
H190/45B	4500	500	595	43	6400	6980	7680	5200	174
H190/50B	5000	500	595	43	5450	5870	6360	4675	196
H220/40B	4000	500	580	50	12000	12000	12000	8350	167
H220/45B	4500	500	580	50	9600	12000	12000	7415	188
H220/50B	5000	500	580	50	8175	8800	9535	6670	210